

Joint Seal Gasket

| Supplier | Brand |
|--|----------------------------------|
| Concrete Sealants, Inc. Tipp City, OH | Conseal CS-102 |
| | Conseal CS-102B |
| | Conseal-202 |
| Hamilton Kent, LLC. Winchester, TN | Tylox SOCL |
| | Tylox SuperSeal |
| Henry Sealant Division Houston, TX | BUTYL-NEK |
| | RAM-NEK |
| Martin Asphalt Company South Houston, TX | Evergrip 990 |
| Rinker Materials Fort Worth, TX | Delta Rubber O-Ring Gasket |
| | Delta Seal Rubber Profile Gasket |
| | Omni-Flex |
| Rinker Materials Gainesville, GA | Delta Rubber O-Ring Gasket |
| | Delta Seal Rubber Profile Gasket |
| Superior Pipe Products, Inc. Depew, OK | Omni-Flex |
| Trelleborg Pipe Seals Park Hills, Inc. Park Hills, MO | Bidco C-56 |

Joint Seal Gasket

Method of Documentation of Acceptance:

By brand and source.

Method of Approval:

- Preformed rubber gaskets accepted on manufacturer certification and independent lab test reports. Bitumen/butyl rubber gaskets must meet the requirements of ASTM C 990. Tubular cross-section, closed cellular gaskets must meet the physical requirements of ASTM D 1056 (Type 2, Class C, Grade 1) and the chemical requirements of ASTM C 990. A test report indicating compliance with these requirements must be submitted.
- Sufficient sample to perform the specification testing must be submitted. Materials submitted for testing shall be accompanied by a Safety Data Sheet (SDS), actual lot/batch certified analysis, and product literature. This product literature should include, as a minimum, such items as: installation procedures, weather restrictions to use, primer requirements, etc.
- After approval for inclusion in the Qualified Products List, samples may be taken at random from shipments. Non-conformance of any material may be cause for the product to be removed from the Qualified Products List.

The manufacturer of privately labeled products must be disclosed.

No information contained in these lists is to be used for promotional purposes.