

Guardrail Delineators

Supplier	Brand
None Approved	
	N/A

Method of Documentation of Acceptance:

By brand and source. Supplier certification shall indicate QPL approved retroreflective sheeting source and brand.

Method of Approval:

Guardrail delineators shall have a minimum reflective area of 8.0 sq. in. per side, be made of galvanized metal with a 12-gauge minimum thickness, and be capable of being bolted to the guardrail web. Glue-on or plastic delineators will not be accepted. The delineator shall have two (2) reflective surfaces and shall use reflective sheeting conforming to ASTM D4956 Types VIII or IX. Reflective sheeting used shall be listed on the Department's Qualified Products List (QPL) 723 Reflective Sheeting.

PROCEDURE TO BE FOLLOWED IN ACQUIRING APPROVAL OF MATERIALS TO BE ADDED TO THE QUALIFIED PRODUCTS LIST:

- The manufacturer shall submit a sample and product information, including printed instructions for application.
- If the guardrail delineator meets the criteria, a letter and unsigned certification agreement will be sent to the manufacturer. The product will be placed on the QPL upon receipt of the signed certification agreement.
- Destination samples will be taken as deemed necessary by the Materials Engineer to assure compliance with specifications.
- Failure of the material in field applications is sufficient reason to reconsider acceptance of the material.
- Suspension of further use and/or removal from the QPL may occur if the Materials Engineer determines that the material is not in compliance with applicable specifications and requirements.
- The manufacturer of privately labeled products must be disclosed.
- No information contained in these lists is to be used for promotional purposes.